## Bureau of Fire Prevention City of Lambertville

18 York Street
Lambertville, NJ 08530
609-397-0110 x23 Fax: 609-397-2203
S. Schlesinger, Fire Official
Ifo@lambertvillenj.org

## **MOBILE FOOD TRUCK OPERATORS**

**Subject:** New Requirements Ventilation Hoods and Suppression Systems in Mobile Enclosed Units (Food Trucks)

The State of New Jersey has updated the Uniform Fire Code, and in accordance with N.J.A.C 5:70-4.7(g) 3, Effective July 1, 2018. All Mobile Food Trucks, where during their cooking operations produce grease laden vapors shall be equipped with a ventilating hood, duct, and automatic fire suppression system designed and installed in accordance with the applicable requirements of NFPA 96.

We created this form with a checklist to make the code clear and easy to follow and reduce any significant changes being required prior to the start of the event.

## **Definition:**

Mobile enclosed unit. A unit of closed construction designed to be driven or towed from place to place, which includes commercial cooking equipment producing grease-laden vapors and which allows for occupancy by the operator. Also known as "mobile canteen."

What this means to you as a Food Truck Operator is that as of the Effective date ALL Fire Safety Permit approvals will be dependent on compliance with these new regulations

## **FOOD TRUCK REQUIREMENTS**

( ) A current hood cleaning report must be available, at the time of the inspection. Hoods need to be clean and free of excess grease accumulation. In accordance with N.J.A.C. 5:70-3, 904.11.6.3, and N.F.P.A. 96. Excessive grease and residue buildup on kitchen exhaust systems, cleaning required.

( ) A Suppression System Inspection Report (Form NJFS 17A) showing that the system was serviced within the last 6 months must be available, at the time of the inspection. The

system must also be tagged by the company that performed the inspection. In
accordance with N.J.A.C. 5:70-3, 904.11.6.4.
( ) When deep fryers are present, a portable Class K fire extinguisher of a minimum 1.5
gallon (6L) capacity will be mounted in the vehicle. In accordance with N.J.A.C 5:70-3,
904.11.5.2 (Depending on the size of your unit and operation more than one may be
required.)
( ) All solid fuel cooking appliances, whether or not under a hood, with fireboxes 5 cubic
feet (0.14 m3) or less in volume shall have a minimum 2.5 gallon (9L) or two 1.5 gallon
(6L) Class "K" wet-chemical portable fire extinguishers located in accordance with
N.J.A.C. 5:70-3, 904.11.5.
( ) A 2A:10B:C Rated Fire Extinguisher with current inspection tag will also be mounted in
the vehicle and readily accessible to the operator.
( ) All gas fittings must be tight and free from leaks; a leak test will be performed prior to
the beginning of your operations. Do not light burners prior to being told to do so by the Inspector.
Please Note: For the safety of the Inspector, if your equipment is hot you may have to shut it down and allow it to cool prior to inspection.
PROPANE TANK REQUIREMENTS:
( ) Propane tanks shall be secured, to prevent falling over.
( ) Propane tanks and equipment shall comply with NFPA 58/2004.
( ) Propane tanks shall not be taken into buildings/tents
( ) All appliances shall be listed and labeled and approved by the fire code official.
(No Homemade Appliances!)
( ) No vehicles shall be parked within 5 feet of tents or canopies.
( ) Suitable barricades shall be provided to maintain a distance of 5 feet between the heat
producing appliance and the public.
( ) Propane tanks between 4 and 40 lbs. shall have an Overfill Protection Device for filling in
NJ.
( ) Propane tanks shall be hydro tested every 12 years, and not dented or badly rusted.
( ) Regulator shall be in good condition and the relief valve shall face away from the public
areas.

discovered that changes may h	ave to be implemented.	
		violation of the fire code is
verifying compliance with this contained in this document. I a	•	,
I attest that the above duties a		·
Failure to meet the above	requirements will resu	It in the denial of your permit.
( ) Hoses shall not create a trippi	ng hazard.	
( ) Hoses shall not be covered with	th grease and shall not be swo	llen.
hose.		
( ) Hoses shall not be frayed or co	racked, and there shall not be	any type of tape on the
operating.		
( ) All plastic type protective caps	o onian be removed nom an pro	parie tariks before

After filling out the check list and signing this form, please show it to the Inspector at the beginning of the Fire Safety Inspection of your Mobile Food Truck. Thank you



Mobile Vendor Form 2022